


		产品技术规格书 Product Technical Specification		文件编号/ Document Number: NYSH/YF-JSGGS-049-2025 版本号/Version: A/0 页数/Page: 1/1
型号	CEFR/SA		电压等级	0.6/1kV
规格	4×25 mm ²		参考标准	IEC 60092-353:2024
产品结构图 Product Structure Diagram				
	1.导体(Conductor) 2.绝缘(Isolation) 3.填充(Filling material) 4.包带(Cable wrapping) 5.外护套(Outer sheath)			
线缆结构/Cable structure				
芯数×截面/Core×Section			4×25 mm ²	
导体/Conductor	材质/Material		镀锡铜丝/Tinned copper wire	
	类型/Type		5 类铜导体/5 types of copper conductors	
	参考外径/Reference outer diameter (mm)		7.3	
绝缘/Isolation	材质/Material		阻燃乙丙橡胶/Flame-retardant ethylene-propylene rubber	
	标称厚度/Reference outer diameter (mm)		1.2	
	最薄点/thinnest point (mm)		0.98	
	颜色/Colour		白色(印黑色数字识别)/White (printed with black numbers for recognition)	
包带/Tape	材质/Material		非吸湿性包带/Non hygroscopic straps	
填充/Fill	材质/Material		非吸湿性填充/Non hygroscopic filling	
金属编织 Metal weaving	材质/Material		/	
	编织密度/Weaving density		/	
外护套 Outer sheath	材质/Material		阻燃氯化聚乙烯橡胶/Flame-retardant chlorinated polyethylene rubber	
	标称厚度/Reference outer diameter (mm)		1.6	
	最薄点/Thinnest point (mm)		1.26	
	颜色/Colour		黑色/Black	
成品最大外径/Maximum finished outer diameter (mm)			31.0	
印字信息/Printing Information			Shanghai Nanyang Cable Co., Ltd CEFR/SA 0.6/1kV 4×25 mm ² ****m	
电气性能/Electrical performance				
耐电压/Withstanding voltage			3.5kV/5min	
导体最高正常运行温度/Max. normal operating temperature of conductor			90℃	
环境温度/Ambient temperature			-35℃~60℃	
编制/日期 Prepared by/Date		审核/日期 Checked by/Date		批准/日期 Approved by/Date
周永森 2025.11.25		丁兴兵 2025.11.25		史军涛 2025.11.25